

CLAIMS

What is claimed is:

1. A casing comprising;
first and second sections,
5 a joint for sealing said sections together to prevent leakage through
said casing,
said joint including a groove in said first section and a tongue
extending from said second section to a distal end in said groove,
said tongue having a slot extending into said distal end thereof for
10 splitting said tongue into first and second forks in frictional engagement with said
groove.
2. A casing as set forth in claim 1 wherein said forks are compressed
together by said groove to narrow said slot from top to bottom to retain said tongue in
15 said groove.
3. A casing as set forth in claim 1 wherein said tongue extends from a
latterly extending flange surface to present a shoulder on either side of said tongue,
said first section presenting a sealing surface on either side of said groove.
20
4. A casing as set forth in claim 3 wherein said groove has a bottom and
said distal end of said tongue is spaced from said bottom when said shoulders engage
said sealing surface.

5. A casing as set forth in claim 4 wherein said distal ends of said forks of said tongue are tapered inwardly to facilitate insertion of said tongue into said groove.

6. A casing as set forth in claim 3 wherein said groove has a bottom and said distal end of said tongue is spaced from said bottom and said shoulders are spaced from said sealing surface.

7. A casing as set forth in claim 6 wherein said distal ends of said forks of said tongue are tapered inwardly to facilitate insertion of said tongue into said groove.

10

8. A casing as set forth in claim 6 wherein said groove includes a narrow bottom portion and a wider lead-in portion, said lead-in portion being spaced from said groove.

9. A casing as set forth in claim 8 including a tapered shoulder connecting said wider portion to said narrow portion.

10. A casing as set forth in claim 1 including a sealing bead extending along each side of said tongue for sealing engagement with said groove.

20

11. A casing as set forth in claim 1 including a snap together connection adjacent said tongue and groove for holding said sections together.

12. A casing as set forth in claim 1 including a blower in said casing for moving air through said casing, and a heat exchanger in said casing for exchanging heat with the fluid flowing through said casing.

5 13. A joint for sealing components together to prevent leakage,
said joint including a groove in said first component and a tongue
extending from said second component to a distal end in said groove,
said tongue having a slot extending into said distal end thereof for
splitting said tongue into first and second forks in frictional engagement with said
10 groove.

14. A casing set forth in claim 13 wherein said forks are compressed
together by said groove to narrow said slot from top to bottom to retain said tongue in
said groove.

15